

WATERPROOF LED DRIVERS



Product Features:

- 12V DC constant voltage
- Input voltage: 170-265V AC 50/60Hz
- Output voltage: 12V DC
- Short circuit, overload, over temperature protection
- Ambient temp: -30 to 50°C
- Flex & plug included
- Maximum recommended distance to light source: 10m

IP67
Rated

2YEAR
Replacement
Warranty

Part No.	Length (mm)	Width (mm)	Depth (mm)	Weight (kg)	Box (cm)	Carton QTY
CLA111011	120	29	21	1.00	23x7x5	1/100
CLA113011	182	30	20	0.38	23x7x5	1/25
CLA115011	178	68	53	1.00	19x11.5x6.5	1/10
CLA1110011	190	68	53	1.10	25x11x6.5	1/10
CLA1115011	242	68	53	1.30	25x16x11	1/10
CLA1120011	235	132.2	65	1.50	29.5x16x8	1/100

Part No.	Description	Watt	Load	Min.Load Per Cable	Max.Load Per Cable
CLA111011	DRIVER LED 12V DC C/VOLTAGE 10W	10W	1-8W	1W	8W
CLA113011	DRIVER LED 12V DC C/VOLTAGE 30W	30W	3-24W	3W	24W
CLA115011	DRIVER LED 12V DC C/VOLTAGE 2x25W	50W	5-40W	2.5W	20W
CLA1110011	DRIVER LED 12V DC C/VOLTAGE 2x50W	100W	10-80W	5.0W	40W
CLA1115011	DRIVER LED 12V DC C/VOLTAGE 2x75W	150W	15-120W	7.5W	60W
CLA1120011	DRIVER LED 12V DC C/VOLTAGE 4x50W	200W	20-160W	5.0W	40W

For CLA115011 / CLA1110011 / CLA1115011 and CLA112011

These drivers are manufactured with a split cable format for carrying increased current for easier connection of multiple loads

Each driver can be used:

- At full load capacity by connecting all cables to one terminal block
- With any combination of split cables (as long as the minimum and maximum loads below are adhered to)
- To minimise the occurrence of voltage drops, the recommended maximum distance from the light source is 10m

FULL load capacity CANNOT be connected to one cable