

- Designed for domestic use where higher lumen output is needed.



High output and low energy

FEATURES

- High lumen output efficiency
- Edison screw and bayonet cap available
- Long lifetime 15000hrs
- Low surface temperature for extra safety

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

APPLICATIONS

- Residential
- Retail
- Cafes
- Restaurants
- Display areas
- Atriums and heritage applications

WARRANTY

- Three years (subject to terms and conditions)

CERTIFICATION	DIMMABLE	DISTRIBUTION	DIMENSIONS(mm)
	 leading and trailing edge		

Part No.	Model No.	Voltage	Watt.	PF	CCT.	Cap	Ra	Lumen	Beam Angle	Lifetime L70B50
112115	YKA67C2-D-15.5W	220-240V	15.5W	0.9	3000K	E27	≥80	1521lm	200°	15000h
112116	YKA67C2-D-15.5W	220-240V	15.5W	0.9	3000K	B22	≥80	1521lm	200°	15000h
112117	YKA67C2-D-15.5W	220-240V	15.5W	0.9	4000K	E27	≥80	1521lm	200°	15000h
112118	YKA67C2-D-15.5W	220-240V	15.5W	0.9	4000K	B22	≥80	1521lm	200°	15000h
112119	YKA67C2-D-15.5W	220-240V	15.5W	0.9	6500K	E27	≥80	1521lm	200°	15000h
112120	YKA67C2-D-15.5W	220-240V	15.5W	0.9	6500K	B22	≥80	1521lm	200°	15000h

[1]Operating Frequency=50/60Hz

[2]Switch Times≥20000

[3] For dimming compatibility please see page 92

