FLEXI SMART 12V SINGLE COLOUR KIT IP44, FLP12V/SBT

2m and 5m smart lighting, white strip kits

Application

Home theatre, bar features, decorative task illumination demanding smart controls

Design Specifications

- Smart LED strip kit
- Dimmable controlled by included remote, or via SAL PIXIE or PIXIE PLUS apps
- Dimming memory function, high performance, stable, even light output
- Pre wired for easy installation, plug-in & ready to use
- Cuttable every 50 mm, 2m or 5m kits, lumens shown are lm/m, strip power 6W/m. NOTE: when cutting LED strips, it is always important to calculate the remaining LED load to reconfirm its compatibility with the existing driver, as driver changes may be required with moderate reduction in loads.
- Choice of 2m and 5m packs available, IP44 strip only, IP20 driver, Heatsink required for system performance Dimming is achieved via the PIXIE or PIXIE PLUS app (strip controller if supplied) or via a SAL Multifunction control. Trailing edge dimmers are not suitable

Performance

Dimmable - **YES**
Dimmer Type - **Remote control or PIXIE**

Technical Specification

Model No.	Input Voltage (V/AC)	Beam Angle (°)	Dim (mm)	Watts per metre (W/m)	Colour Temp. (K)	LEDs Per Metre
FLP12V2M/WW/SBT	240	115	2000(L) x 8(W) x 2.5(H)	6	3000	60
FLP12V2M/NDL/SBT	240	115	2000(L) x 8(W) x 2.5(H)	6	5000	60
FLP12V5M/WW/SBT	240	115	5000(L) x 8(W) x 2.5(H)	6	3000	60
FLP12V5M/NDL/SBT	240	115	5000(L) x 8(W) x 2.5(H)	6	5000	60

PDF Prepared: 19.3.2021 8:25am
Last page update: Oct 2020

WARM WHITE 3000K

DAYLIGHT 5000K

Technical Specification

Model No.	CRI
FLP12V2M/WW/SBT	80
FLP12V2M/NDL/SBT	80
FLP12V5M/WW/SBT	80
FLP12V5M/NDL/SBT	80

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

Cuttable locations

PDF Prepared: 19.3.2021 8:25am
Last page update: Oct 2020