



SLIMLINE SEAMLESS TC LINKABLE SL9706 - 4/22W


TC SEAMLESS SLIMLINE

Application

Great for commercial shop spaces, home pantries, walk-in wardrobes

Design Specifications

- Selectable colour temperature 3000K, 4000K, 5500K, beam distribution 105 degree, CRI > 80
- Polycarbonate body profile and opal diffuser
- Integral constant current non-dimmable driver
- Individual switch control, plug and play flex and plug included
- Maximum connections: 280TC x 55, 540TC x 25, 840TC x 17, 1140TC x 12, 1440TC x 10 UNITS, Maximum mixed connections 240W
- Accessories: SL9706/32CM LINK (L 320mm)
SL9706/76CM LINK (L 760 mm)



Technical Specification




Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	CCT (K)	CRI	Beam Angle (°)
SL9706/280TC	240	4	300/380/300	3000/4000/5500	80	105
SL9706/540TC	240	9	750/800/750	3000/4000/5500	80	105
SL9706/840TC	240	13	1050/1200/1050	3000/4000/5500	80	105
SL9706/1140TC	240	18	1550/1600/1600	3000/4000/5500	80	105
SL9706/1440TC	240	22	1800/2000/1800	3000/4000/5500	80	105

Model No.	Dim (mm)	Body Colour	VEET
SL9706/280TC	280(L) x 23(W) x 36(H)	WHITE	
SL9706/540TC	540(L) x 23(W) x 36(H)	WHITE	
SL9706/840TC	840(L) x 23(W) x 36(H)	WHITE	YES
SL9706/1140TC	1140(L) x 23(W) x 36(H)	WHITE	YES
SL9706/1440TC	1440(L) x 23(W) x 36(H)	WHITE	YES

IMPORTANT, where CCT selection switching is provided, it is important to switch OFF the SUPPLY before the CCT selection is made, otherwise equipment damage may occur.

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions



Maximum connections
Mixed connections maximum 240W

SL9706/280IC	1 2 3 4...	55pcs
SL9706/540IC	1 2 3 4...	25pcs
SL9706/840IC	1 2 3 4...	17pcs
SL9706/1140IC	1 2 3 4...	12pcs
SL9706/1440IC	1 2 3 4...	10pcs

THE NEW ESS106 IS SMALL IN SIZE BUT BIG ON FEATURES.



For more
information
please
scan me

